

SAVSOL RACETRACK XL 20W-50

DESCRIPTION

SAVSOL RACETRACK XL 20W-50 is a premium high performance engine oil especially formulated for new generation four stroke engines. It is fortified with high level of detergent & dispersant additives and Viscosity Modifier which provides maximum protection for the engines.

APPLICATIONS:

SAVSOL RACETRACK XL 20W-50 is suitable for lubrication of four-stroke cars/SUV engines under moderate to severe operating conditions.

SPECIFICATIONS:

SAVSOL RACETRACK XL 20W-50 exceeds requirements of the following performance specifications:

> API SL/CF

CHARACTERISTICS:

SAVSOL RACETRACK XL 20W-50 having the outstanding features of:

- Excellent control on Engine wear and deposits.
- The high TBN effectively neutralizes the acids of combustion and prevents acid attack.
- Increased oil drain interval due to good thermal resistance.
- Retention of viscosity over vide temperature ranges.



Savita Oil Technologies Ltd 66/67, Nariman Bhavan, Nariman Point, Mumbai 400 021, India. T: +91 22 2288 3061 / 64 F: +91 22 2202 9364 W: www. savsol.com E: customersupport@savita.com





SAVSOL RACETRACK XL 20W-50

TECHNICAL SPECIFICATIONS: SAVSOL RACETRACK XL 20W-50

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Colour ASTM	Visual	Red
Density @ 29.5°C, gm/cc	D4052	0.8870
Kinematic Viscosity @ 40ºC, cSt	D445	165.30
Kinematic Viscosity @ 100ºC, cSt	D445	17.80
Viscosity Index	D2270	118
Flash Point, ^o C	D92	240
Pour Point, ^o C	D97	-21
Total Base Number, mg KOH/gm	D2896	5.89
CCS Viscosity @ -15°C, cP	D5293	6800

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

<u>STORAGE</u>

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFTEY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.01 dated 12th Jan.2024.



Savita Oil Technologies Ltd 66/67, Nariman Bhavan, Nariman Point, Mumbai 400 021, India. T: +91 22 2288 3061 / 64 F: +91 22 2202 9364 W: www. savsol.com E: customersupport@savita.com

