

# SAVSOL SYNTH RACETRACK 5W-40

## **DESCRIPTION:**

**SAVSOL SYNTH RACETRACK 5W-40** is synthetic motor oil specially designed for high end cars/SUV's running on petrol as well as diesel fuels. Its unique additive technology helps high-performance cars operate at maximum efficiency in more rough conditions. It is suitable for Turbo charged & Direct Injection engines where the engines observe high stress conditions.

## **APPLICATION:**

**SAVSOL SYNTH RACETRACK 5W-40** Engine Oil recommended for latest new generation vehicles manufactured by all leading OEMs of Toyota, Mahindra, Tata, GM, Ford, Honda, Suzuki, Renault, Hyundai, Nissan etc.

## **SPECIFICATIONS & APPROVALS:**

**SAVSOL SYNTH RACETRACK 5W-40** exceeds the requirements of the following performance specifications:

- |                 |                 |                       |
|-----------------|-----------------|-----------------------|
| ➤ API SN/CF     | ➤ ACEA A3/B3-10 | ➤ RENAULT RN0710/0700 |
| ➤ ACEA A3/B4-08 | ➤ MB 229.3      | ➤ VW 502.00/505.00    |

## **ADVANTAGES:**

**SAVSOL SYNTH RACETRACK 5W-40** offers the following advantages:

- Superior engine protection on critical engine parts.
- Exceptional cleansing even at longer drain interval periods.
- Helps to remove the sludge faster than the conventional oils.
- Use of high performance Hydrocracked base oils provides low oil top-up.
- Improves engine efficiency and reduce the deposits.
- Neutralizes the corrosive combustion acids efficiently and protects the engine parts.
- Its synthetically engineered formula most advanced additives provide excellent low temperature flow properties and oxidation Stability.
- Its highly effective & robust synthetic formula reduces the friction and maximizes the engine performance.
- Offers maximum protection in very hot and extremely cold conditions.
- Provides complete engine protection across different engine speeds & conditions.

# SAVSOL SYNTH RACETRACK 5W-40

## **TECHNICAL SPECIFICATIONS: SAVSOL SYNTH RACETRACK 5W-40**

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Colour ASTM	D1500	L 3.0
Density @ 29.5°C, gm/cc	D4052	0.8420
Kinematic Viscosity @ 40°C, cSt	D445	85.28
Kinematic Viscosity @ 100°C, cSt	D445	14.18
Viscosity Index	D2270	172
Flash Point, °C	D92	232
Pour Point, °C	D97	-33
Total Base Number, mg KOH/gm	D2896	9.62
CCS Viscosity @ -30°C, cP	D5293	5820

*The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.*

## **STORAGE**

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

## **ENVIRONMENT, HEALTH AND SAFETY**

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.01 dtd 12<sup>th</sup> Jan2024.