

# SAVSOL FRONT FORK

### **DESCRIPTION:**

**SAVSOL FRONT FORK** is blended with high quality base stocks and performance additives. Its effective additive chemistry provides excellent dampening effect and ensures outstanding viscosity stability.

### **APPLICATION:**

**SAVSOL FRONT FORK** is recommended for front forks in two wheelers under severe conditions.

### **ADVANTAGES:**

**SAVSOL FRONT FORK** offers the following advantages:

- High Viscosity index and its super viscosity & temperature properties ensures outstanding viscosity stability.
- Excellent anti-wear, anti-friction properties effectively protecting parts of the forks
- Possesses excellent dampening effect and gives uniform effect in operation.
- Outstanding anti-oxidation stability helps extending the service life of parts.
- Unique balanced formulation gives good foam stability and rubber compatibility ensuring smooth application.
- Highly shear stable product gives trouble free operation for life-time.
- It's very low pour point and air retention gives year round use in all weather conditions.





# SAVSOL FRONT FORK

## **TECHNICAL SPECIFICATIONS:** SAVSOL FRONT FORK

PROPERTIES	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Bright & Clear
Colour	ASTM D1500	L 0.5
Density @ 29.5 °C, gm/cc	ASTM D4052	0.8300
Kin. Viscosity @ 40 °C, cSt	ASTM D445	15.20
Kin. Viscosity @ 100 °C, cSt	ASTM D445	3.81
Viscosity Index	ASTM D2270	148
Flash Point, COC, <sup>0</sup> C	ASTM D92	190
Pour Point, <sup>0</sup> C	ASTM D97	- 33

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

#### **STORAGE**

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

### ENVORNMENT, HEALTH AND SAFTEY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.01 dtd 12th Mar.2019.

