



SAVSOL UTTO

DESCRIPTION:

SAVSOL UTTO is a premium high performance Universal Tractor Transmission Oil (UTTO) specially designed with advance anti-wear and extreme pressure technology for tractors and off-road equipment's.

APPLICATION:

SAVSOL UTTO is recommended for Tractors, Agriculture & Forest Equipment transmissions, drives and hydraulic systems.

SPECIFICATIONS & APPROVALS:

SAVSOL UTTO meets the requirements of:

- Massey Ferguson
- Ford New Holland
- J.I. Case / Case International
- Kubota
- John Deere
- Volvo

SAVSOL UTTO meets requirements of following transmission OEM's:

- Catterpillar-T02
- Plessey Sundstrand
- Hydraulic OEMs : Sperry Vickers
- ABEX Dennison

ADVANTAGES:

SAVSOL AUTOGEAR EP 140 delivers following advantages:

- Outstanding low temperature performance.
- Excellent resistance to oxidation breakdown caused by heat.
- Exceptional anti wear properties.
- Resistance to rust and corrosion.
- Excellent system cleanliness.

SAVSOL UTTO

TECHNICAL SPECIFICATIONS: SAVSOL UTTO

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear
Colour ASTM	D1500	L 1.5
Density @ 29.5°C, gm/cc	D4052	0.8470
Kinematic Viscosity @ 40°C, cSt	D445	61.20
Kinematic Viscosity @ 100°C, cSt	D445	9.714
Viscosity Index	D2270	144
Flash Point, °C	D92	244
Pour Point, °C	D97	-42

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVORNMENT, HEALTH AND SAFTEY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.01 dtd 19th Mar.2019