



SAVSOL AUTOGEAR EP 140

DESCRIPTION:

SAVSOL AUTOGEAR EP 140 is a high performance gear oil designed to provide effective lubrication in wide range of automotive and transmissions and axle drives where GL-4 performance is required. The advance formula with hi quality extreme pressure additive technology provides all-rounder protection of gears, its components against wear and scoring.

APPLICATION:

SAVSOL AUTOGEAR EP 140 is recommended for transaxles requiring GL-4 performance, cars, mini trucks, construction, mining and agriculture equipment's. It can be used in applications where spiral bevel gears operating under moderate to severe speeds and loads and axles with hypoid gears.

SPECIFICATIONS & APPROVALS:

SAVSOL AUTOGEAR EP 140 meet the following performance specification

- API GL-4

ADVANTAGES:

SAVSOL AUTOGEAR EP 140 delivers following advantages:

- Excellent seal compatibility.
- Protection against rust and corrosion.
- Outstanding thermal and chemical stability.
- Excellent extreme pressure and anti-wear properties.

SAVSOL AUTOGEAR EP 140

TECHNICAL SPECIFICATIONS: SAVSOL AUTOGEAR EP 140

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Colour ASTM	D1500	L 4.5
Density @ 29.5°C, gm/cc	D4052	0.8940
Kinematic Viscosity @ 40°C, cSt	D445	409
Kinematic Viscosity @ 100°C, cSt	D445	28.83
Viscosity Index	D2270	98
Flash Point, °C	D92	252
Pour Point, °C	D97	-6

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVORNMENT, HEALTH AND SAFTEY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.01 dtd 19th Mar.2019