



# SAVSOL AUTOGEAR HD 85W-140

## **DESCRIPTION:**

**SAVSOL AUTOGEAR HD 85W-140** is high quality extreme pressure type multigrade gear lubricant specially designed for heavy commercial vehicles and other automotive equipment's operated under high-speed high-shock load, high-speed low-torque and low-speed high-torque conditions.

## **APPLICATION:**

**SAVSOL AUTOGEAR HD 85W-140** is recommended for non-synchronised manual transmissions and axle drives of heavy commercial vehicles as well as hypoid gears in passenger cars and other equipment's.

## **SPECIFICATIONS & APPROVALS:**

**SAVSOL AUTOGEAR HD 85W-140** oil meet the following performance specification

- API GL-5
- ZF TE-ML 07A

## **ADVANTAGES:**

**SAVSOL AUTOGEAR HD 85W-140** delivers following advantages:

- Excellent load carrying capacity.
- Excellent rust and corrosion protection.
- Superior oxidation stability with longer drain intervals.
- Outstanding protection of gears against wear and enhances durability & reliability.
- Excellent seal compatibility helps to minimise leakages and reduces chances of contamination.

# SAVSOL AUTOGEAR HD 85W-140

## **TECHNICAL SPECIFICATIONS: SAVSOL AUTOGEAR HD 85W-140**

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Colour ASTM	D1500	L 4.5
Density @ 29.5°C, gm/cc	D4052	0.8900
Kinematic Viscosity @ 40°C, cSt	D445	356.70
Kinematic Viscosity @ 100°C, cSt	D445	26.06
Viscosity Index	D2270	97
Flash Point, °C	D92	240
Pour Point, °C	D97	-6

*The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.*

## **STORAGE**

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

## **ENVORNMENT, HEALTH AND SAFTEY**

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.01 dtd 19<sup>th</sup> Mar.2019