



SAVSOL PREMIUM SELECT 2T

DESCRIPTION:

SAVSOL PREMIUM SELECT 2T is high quality engine oil specifically designed for 2-stroke petrol engines having direct oil injection or premix systems.

APPLICATION:

SAVSOL PREMIUM SELECT 2T Engine Oil recommended for motorcycles, scooters and mini speed boats having two-stroke engines.

SPECIFICATIONS:

SAVSOL PREMIUM SELECT 2T meets the specification requirements of:

- API TC
- JASO FC

ADVANTAGES:

SAVSOL PREMIUM SELECT 2T offers the following advantages:

- Smoke free exhaust.
- Outstanding wear protection.
- Extends engine life without power loss.
- Easily mixes with fuel and forms homogeneous mixture even at low temperature.

SAVSOL PREMIUM SELECT 2T

TECHNICAL SPECIFICATIONS: SAVSOL PREMIUM SELECT 2T

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Colour ASTM	Visual	Green
Density @ 29.5°C, gm/cc	D4052	0.8550
Kinematic Viscosity @ 40°C, cSt	D445	66.87
Kinematic Viscosity @ 100°C, cSt	D445	9.611
Viscosity Index	D2270	124
Flash Point, °C	D92	110
Pour Point, °C	D97	-12
Total Acid Number, mg KOH/gm	D664	0.32

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVORNMENT, HEALTH AND SAFTEY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.01 dtd 12th Mar.2019.