



SAVSOL SYNTH AUTOGEAR 75W90

DESCRIPTION:

SAVSOL SYNTH AUTOGEAR 75W90 is a premium grade synthetic gear lubricant for heavy duty, extreme pressure (EP) applications which is formulated using synthetic base stocks with high viscosity index & low pour points. Its advance additive technology protects gears and bearings operated under a wide variety of load conditions.

APPLICATIONS:

SAVSOL SYNTH AUTOGEAR 75W90 is recommended for Manual Transmission where EP type of lubricants are required, also recommended for limited slip differentials and transfer cases.

SPECIFICATIONS:

SAVSOL SYNTH AUTOGEAR 75W90 meets or exceeds performance specification requirements of:

- API Service GL-4 & MT -1
- MIL -L-2105D /MIL -PRF -2105E
- Mercedes Benz Sheet 235.6
- ZF TE ML 05/07/08

ADVANTAGES:

SAVSOL SYNTH AUTOGEAR 75W90 offers the following advantages:

- “All-season” lubrication and extended drain intervals.
- Extremely high film strength.
- Superior low temperature performance.
- Reduces sludge and varnish formations.

SAVSOL SYNTH AUTOGEAR 75W90

TECHNICAL SPECIFICATIONS: SAVSOL SYNTH AUTOGEAR 75W-90

| PROPERTIES | ASTM TEST METHOD | TYPICAL VALUES |
|----------------------------------|------------------|----------------|
| Appearance | Visual | Clear & Bright |
| Colour ASTM | D1500 | L 0.5 |
| Density @ 29.5°C, gm/cc | D4052 | 0.8480 |
| Kinematic Viscosity @ 40°C, cSt | D445 | 76.20 |
| Kinematic Viscosity @ 100°C, cSt | D445 | 14.72 |
| Viscosity Index | D2270 | 204 |
| Flash Point, °C | D92 | 224 |
| Pour Point, °C | D97 | -42 |

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.01 dtd 19th Mar.2019