



SAVSOL UTTO PLUS

DESCRIPTION:

SAVSOL UTTO PLUS is a premium multipurpose Universal Tractor Transmission Oil (UTTO) specially designed with synergistic combination of additive and synthetic base stocks with high viscosity index which provides optimum protection at extreme load conditions and elevated temperatures for tractors and off-road equipments. It is designed for achieving the optimum performance of Agricultural & commercial tractors operating in a wide range of environments & conditions.

APPLICATION:

SAVSOL UTTO PLUS is recommended for all type of Tractors, Agriculture & Forest Equipment transmissions, Backhoe Loaders, Wheel Loaders, Earth moving equipment's, drives and hydraulic systems. It is very much suitable for wet break applications.

SPECIFICATIONS & APPROVALS:

SAVSOL UTTO PLUS meets the requirements of:

- Massey Ferguson MF1145
- Allison C4
- API GL-4
- Ford New Holland
- John Deere J20C/D
- J.I. Case / Case International
- Volvo WB 101

ADVANTAGES:

SAVSOL UTTO PLUS delivers following advantages:

- Excellent control on brake chatter noise.
- Its enhanced frictional properties provide optimum clutch performance & wet brake applications.
- Smooth wet brake and power take-off operation with control on stick-slip & squawk.
- High viscosity index and shear stability which gives consistency in operation.
- Excellent thermal and oxidation stability.
- Extended seal life span and service life of equipment.
- Superior low temperature properties which delivers effective lubrication even in cold weather conditions.
- Outstanding anti-wear performance which protects equipment components against wear and scuffing.
- Excellent filterability in hydraulic systems improves equipment uptime and reduces maintenance time.



SAVSOL UTTO PLUS

TECHNICAL SPECIFICATIONS: SAVSOL UTTO PLUS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Bright & Clear
Colour ASTM	D1500	L2.0
Density @ 29.5°C, gm/cc	D4052	0.8590
Kinematic Viscosity @ 40°C, cSt	D445	61.30
Kinematic Viscosity @ 100°C, cSt	D445	9.75
Viscosity Index	D2270	143
Flash Point, °C	D92	234
Pour Point, °C	D97	-33

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

STORAGE:

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY:

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 30thJun.2020