



SAVSOL PREMIUM PLUS 4T 15W-50

DESCRIPTION:

SAVSOL PREMIUM PLUS 4T 15W-50 is high performance, synthetic technology motorcycle engine oil specially engineered for high power 4-stroke motorcycles.

Due to its synergistic combination of premium quality base stocks and performance additive system, it delivers optimum performance at elevated temperatures and harsh environmental conditions with smooth and comfortable riding experience.

SAVSOL PREMIUM PLUS 4T 15W-50 protects your high performance motorcycle engine from heat and friction which leads to longer engine life and maximum power output. It offers smooth clutch operation and superior engine cleanliness. Also, it helps to reduce vibrations and engine noise.

APPLICATION:

SAVSOL PREMIUM PLUS 4T 15W-50 is specially recommended for Cruiser Bikes and Street Bikes of all leading OEM's recommending SAE 15W-50 engine oil.

SPECIFICATIONS:

SAVSOL PREMIUM PLUS 4T 15W-50 meets & exceeds the requirements and performance specifications of :

- API SN
- JASO MA2

ADVANTAGES:

SAVSOL PREMIUM PLUS 4T 15W-50 offer the following advantages:

- BS-VI compatible.
- Quick cold start.
- Delivering high power.
- Keeps engine cool & clean.
- Ultimate protection to engine, gear & clutch.
- Reduce heat & friction.
- Superior protection from wear & rust.
- Protects from friction & wear.
- Excellent seal compatibility.
- Catalyst compatible.

SAVSOL PREMIUM PLUS 4T 15W-50

TECHNICAL SPECIFICATIONS: SAVSOL PREMIUM PLUS 4T 15W-50

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Colour ASTM	D1500	L2.0
Density @ 29.5°C, gm/cc	D4052	0.8530
Kinematic Viscosity @ 40°C, cSt	D445	136
Kinematic Viscosity @ 100°C, cSt	D445	17.91
Viscosity Index	D2270	147
Total Base Number, mg KOH/gm	D2896	6.04
Flash Point, °C	D92	248
Pour Point, °C	D97	-27

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVORNMENT, HEALTH AND SAFTEY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 20th Oct.2020