

# SAVSOL R2U COOLANT

## **DESCRIPTION:**

**SAVSOL R2U COOLANT** is pre diluted READY-TO-USE coolant for wide range of radiators in various applications. The special inhibitor formula provides excellent heat transfer from engine components and excellent corrosion protection of all engine and cooling components. It is free from nitrile, amines, silicates, borates and phosphates.

## **APPLICATION:**

**SAVSOL R2U COOLANT** is recommended for use in radiators of all advanced engines of trucks, buses, LCVs, cars, SUVs, tractors, earth moving and construction equipment's and highly loaded engines used in tropical regions where freezing protection is not required.

## **SPECIFICATIONS:**

**SAVSOL R2U COOLANT** complies specification of: JIS K2234-2006 Class II.

## **ADVANTAGES:**

**SAVSOL R2U COOLANT** offers the following Advantages:

### **Advantages:**

- Easy to use.
- Excellent cooling.
- Low Evaporation.
- Superior chemical stability.
- No scale formation and No foaming.
- Outstanding heat transfer.
- Superior seal compatibility.
- Excellent corrosion protection.

# SAVSOL R2U COOLANT

## **TECHNICAL SPECIFICATIONS: SAVSOL R2U COOLANT**

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Colour	Visual	Green
Density @ 29.5°C	D 1122	1.060
pH Value	D 1287	8.20
Boiling Point	D 1120	108

## **STORAGE**

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

## **ENVIRONMENT, HEALTH AND SAFETY**

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

*Rev.No.00 dtd 15<sup>th</sup> March. 2019.*