

# SAVSOL ESTER5 ESTER SCOOTER 4(AT) 10W-30

### **DESCRIPTION:**

**SAVSOL ESTER5 ESTER SCOOTER 4(AT) 10W-30** is a high-performance synthetic 4-stroke engine oil, specifically designed for modern scooters equipped with automatic transmissions and dry clutches. Due to the compact and enclosed nature of scooter engines, which operate at higher temperatures, they require specially formulated oils, as standard motorcycle oils may not offer sufficient protection. Blended with synthetic base stocks and enhanced by a low-friction formula, this oil ensures superior performance. Its advanced additive technology guarantees quick throttle response and a smooth riding experience, even in demanding city-driving conditions.

### **APPLICATION:**

**SAVSOL ESTER5 ESTER SCOOTER 4(AT) 10W-30** is highly recommended for modern scooters with automatic transmissions and dry clutches, meeting API SN and JASO MB quality standards.

#### **SPECIFICATION:**

SAVSOL ESTER5 ESTER SCOOTER 4(AT) 10W-30 meets the specification requirements of:

- > API SN
- JASO MB

### **ADVANTAGES**:

SAVSOL ESTER5 ESTER SCOOTER 4(AT) 10W-30 has following benefits:

- The **low-friction formula** reduces engine friction, providing instant pick-up and offering potential fuel economy benefits.
- Enduring thermo-oxidative stability protects compact and enclosed scooter engines that operate at higher temperatures.
- The **special formula** keeps engine parts cleaner, thereby extending the engine's lifespan.



Savita Oil Technologies Limited 66/67, Nariman Bhavan, Nariman Point, Mumbai – 4000 021 T: +91 22 2281 8042, E : <u>customersupports@savita.com</u> www.savita.com www.savsol.com



## SAVSOL ESTER5 ESTER SCOOTER 4(AT) 10W-30

## **TECHNICAL SPECIFICATIONS**

PROPERTIES	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Bright & Clear
Density @ 29.5 °C, gm/cc	ASTM D4052	0.8519
Kinematic Viscosity @ 40 °C, cSt	ASTM D445	64.58
Kinematic Viscosity @ 100 °C, cSt	ASTM D445	10.27
Viscosity Index	ASTM D2270	144
Flash Point, COC, °C	ASTM D92	238
Pour Point, °C	ASTM D97	-30

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

#### Storage:

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

#### Environment, Health and Safety

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 29th June .2024.



Savita Oil Technologies Limited 66/67, Nariman Bhavan, Nariman Point, Mumbai – 4000 021 T: +91 22 2281 8042, E : <u>customersupports@savita.com</u> www.savita.com www.savisol.com