

## SAVSOL ESTER5 ESTERMAX 5000 4T 20W-50

### DESCRIPTION:

**SAVSOL ESTER5 ESTERMAX 5000 4T 20W-50** is a premium 4-stroke motorcycle oil crafted from top-tier base stocks. With advanced additive and **ESTER5** Technology, this oil provides thorough protection for all lubricated parts and enhances engine performance, particularly during highway rides.

### APPLICATION:

**SAVSOL ESTER5 ESTERMAX 5000 4T 20W-50** is recommended to use in high performance motorcycles where SAE 20W-50 viscosity grade is recommended.

### SPECIFICATIONS:

**SAVSOL ESTER5 ESTERMAX 5000 4T 20W-50** meets the specification requirements of:

- API SL
- JASO MA2

### ADVANTAGES:

- It forms a robust shield against friction and wear, safeguarding critical engine components from premature deterioration and it helps extended engine life.
- With a broad viscosity range, it adapts effortlessly to diverse riding conditions and engine types.
- Engineered with advanced thermal and oxidation stability, this motorcycle oil withstands the rigors of high temperatures and extended use without breaking down.
- It provides exceptional corrosion protection, safeguarding vital engine components from the harmful effects of moisture and environmental contaminants.

# SAVSOL ESTER5 ESTERMAX 5000 4T 20W-50

## TECHNICAL SPECIFICATIONS

PROPERTIES	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Bright & Clear
Density @ 29.5 °C, gm/cc	ASTM D4052	0.8598
Kinematic Viscosity @ 40 °C, cSt	ASTM D445	143.90
Kinematic Viscosity @ 100 °C, cSt	ASTM D445	17.83
Viscosity Index	ASTM D2270	137
Flash Point, COC, °C	ASTM D92	242
Pour Point, °C	ASTM D97	-27

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

### Storage

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

### Environment, Health and Safety

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 09<sup>th</sup> May.2024.