

SAVSOL GREASE AP-3 PLUS

DESCRIPTION:

SAVSOL GREASE AP-3 PLUS is a multipurpose, premium-quality lithium grease specifically formulated to meet the demanding needs of heavy-duty trucking, as well as a variety of automotive and industrial applications. This grease provides exceptional lubrication and protection, making it suitable for use in a wide range of environments and operating conditions.

APPLICATION:

SAVSOL GREASE AP-3 PLUS is recommended for lubrication of wheel bearings, chassis components of automotive vehicles, ball joints, couplings, linkages, axles, universal joints, bushings, etc. and all other mechanical parts used in automotive, industrial and other services.

SPECIFICATION:

SAVSOL GREASE AP-3 PLUS meets the following performance specification requirement:

- NLGI # 3

ADVANTAGES:

SAVSOL GREASE AP-3 PLUS offers the following advantages:

- High drop point and high operating temperature.
- Superior protection against rust and corrosion.
- Excellent thermal and oxidation stability.
- Longer bearing life and prevents leak out from bearings.
- Outstanding mechanical stability and resistance to softening delivers long grease life.
- Excellent water washout property gives extended component protection and prolonged equipment life.

SAVSOL GREASE AP-3 PLUS

TECHNICAL SPECIFICATIONS

| PROPERTIES | ASTM TEST METHOD | TYPICAL VALUES |
|---------------------------|------------------|----------------|
| Appearance | Visual | Homogeneous |
| Texture | Visual | Smooth |
| Colour | Visual | Light Yellow |
| NLGI # | -- | 3 |
| Thickener Type | -- | Lithium |
| Worked Penetration @ 25°C | ASTM D217 | 240 |
| Dropping Point °C, | ASTM D566 | 190 |

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 17th July 2024