

SAVSOL ESTER5 ESTERMAX 7000 4T 15W-50

DESCRIPTION:

SAVSOL ESTERS ESTERMAX 7000 4T 15W-50 is a cutting-edge engine oil, meticulously crafted for 4-stroke motorbikes. This advanced oil is engineered with high-quality base oils, innovative additives, and **ESTER5** technology to deliver outstanding performance and protection. This oil ensures outstanding performance and protection under various riding conditions including highway ride.

APPLICATION:

SAVSOL ESTER5 ESTERMAX 7000 4T 15W-50 is suitable for high-end bikes like Royal Enfield, Harley Davidson, etc. It is also recommended for new-generation 4-stroke motorcycles from all other leading OEMs recommending 15W-50 grade engine oil.

SPECIFICATION:

SAVSOL ESTER5 ESTERMAX 7000 4T 15W-50 meets the specification requirements of:

- > API SN
- JASO MA2

ADVANTAGES:

SAVSOL ESTER5 ESTERMAX 7000 4T 15W-50 has following benefits:

- High Load Capacity: Engineered to handle high loads and extreme conditions, making it ideal for powerful and high-performance engines.
- Meets Latest Engine Demands: Formulated to meet the stringent requirements of advanced, powerful motorcycle engines, ensuring top performance and reliability.
- **Thermal Stability**: Maintains stability and performance under high-temperature conditions, crucial for high-performance and demanding engines.
- Versatile Performance: Ensures superior performance and durability under various riding conditions, making it ideal for both everyday use and extreme riding environments.





SAVSOL ESTER5 ESTERMAX 7000 4T 15W-50

TECHNICAL SPECIFICATIONS

PROPERTIES	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Bright & Clear
Density @ 29.5 °C, gm/cc	ASTM D4052	0.8540
Kinematic Viscosity @ 40 °C, cSt	ASTM D445	135.0
Kinematic Viscosity @ 100 °C, cSt	ASTM D445	18.09
Viscosity Index	ASTM D2270	149
Flash Point, COC, °C	ASTM D92	244
Pour Point, °C	ASTM D97	-30

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

Storage:

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

Environment, Health and Safety

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 29th June .2024.

