

SAVSOL AUTOGEAR 80W-90

DESCRIPTION:

SAVSOL AUTOGEAR 80W-90 is a multipurpose premium quality EP gear lubricant for automotive applications specially designed to provide optimum benefits in mechanical transmissions, axles and gear boxes of heavy commercial vehicles operated in moderate and severe conditions.

APPLICATION:

SAVSOL AUTOGEAR 80W-90 is recommended for transmission & axles of all types of heavy commercial as well as other automotive vehicles where GL-4 performance is required.

SPECIFICATION & APPROVALS:

SAVSOL AUTOGEAR 80W-90 meet the following performance specification requirements:

- API GL-4

ADVANTAGES:

SAVSOL AUTOGEAR 80W-90 offers the following benefits:

- Excellent extreme pressure and anti-wear properties.
- Outstanding protection to gear and its components, long life and durability.
- Good anti-foam properties and film strength.
- Superior protection from rust and corrosion.
- Excellent seal compatibility.

SAVSOL AUTOGEAR 80W-90

TECHNICAL SPECIFICATIONS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUE
Appearance	Visual	Bright & Clear Fluid
Colour ASTM	D1500	L 3.0
Density @ 29.5 °C, gm/cm ³	D4052	0.8740
Kinematic Viscosity @ 40°C, cSt	D7042	163.0
Kinematic Viscosity @ 100°C, cSt	D7042	16.60
Viscosity Index	D2270	107
Flash Point, COC, °C	D92	210
Pour Point, °C	D97	-33

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

Storage:

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

Environment, Health, and Safety

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point.
- This product is unlikely to present any safety & health hazard when effectively used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 11th July 2025.