

SAVSOL AUTOGEAR EP 140

DESCRIPTION:

SAVSOL AUTOGEAR EP 140 is a high performance gear oil designed to provide effective lubrication in wide range of automotive and transmissions and axle drives where GL-4 performance is required. The advance formula with hi quality extreme pressure additive technology provides all-rounder protection of gears, its components against wear and scoring.

APPLICATION:

SAVSOL AUTOGEAR EP 140 is recommended for transaxles requiring GL-4 performance, cars, mini trucks, construction, mining and agriculture equipment's. It can be used in applications where spiral bevel gears operating under moderate to severe speeds and loads and axles with hypoid gears.

SPECIFICATION & APPROVALS:

SAVSOL AUTOGEAR EP 90 meet the following performance specification requirements:

- API GL-4

ADVANTAGES:

SAVSOL AUTOGEAR EP 90 offers the following benefits:

- Excellent seal compatibility.
- Protection against rust and corrosion.
- Outstanding thermal and chemical stability.
- Excellent extreme pressure and anti-wear properties.

SAVSOL AUTOGEAR EP 140

TECHNICAL SPECIFICATIONS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUE
Appearance	Visual	Bright & Clear Fluid
Colour ASTM	D1500	L 4.5
Density @ 29.5 °C, gm/cm ³	D4052	0.8940
Kinematic Viscosity @ 40°C, cSt	D7042	409
Kinematic Viscosity @ 100°C, cSt	D7042	28.83
Viscosity Index	D2270	98
Flash Point, COC, °C	D92	252
Pour Point, °C	D97	-6

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

Storage:

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

Environment, Health, and Safety

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point.
- This product is unlikely to present any safety & health hazard when effectively used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 11th July 2025.