

SAVSOL AUTOGEAR HD 85W-140

DESCRIPTION:

SAVSOL AUTOGEAR HD 85W-140 is high quality extreme pressure type multigrade gear lubricant specially designed for heavy commercial vehicles and other automotive equipment's operated under high-speed high-shock load, high-speed low-torque and low-speed high-torque conditions.

APPLICATION:

SAVSOL AUTOGEAR HD 85W-140 is recommended for non-synchronised manual transmissions and axle drives of heavy commercial vehicles as well as hypoid gears in passenger cars and other equipment's.

SPECIFICATION & APPROVALS:

SAVSOL AUTOGEAR HD 85W-140 oil meet the following performance specification

- API GL-5
- ZF TE-ML 07A

ADVANTAGES:

SAVSOL AUTOGEAR HD 85W-140 offers the following advantages:

- Excellent load carrying capacity.
- Excellent rust and corrosion protection.
- Superior oxidation stability with longer drain intervals.
- Outstanding protection of gears against wear and enhances durability & reliability.
- Excellent seal compatibility helps to minimise leakages and reduces chances of contamination.

SAVSOL AUTOGEAR HD 85W-140

TECHNICAL SPECIFICATIONS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Colour ASTM	D1500	L 4.5
Density @ 29.5°C, gm/cc	D4052	0.8900
Kinematic Viscosity @ 40°C, cSt	D445	356.70
Kinematic Viscosity @ 100°C, cSt	D445	26.06
Viscosity Index	D2270	97
Flash Point, °C	D92	240
Pour Point, °C	D97	-6

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 14th Jan 2025