

## SAVSOL ESTER5 RACETRACK DIESEL 15W-40

### DESCRIPTION:

**SAVSOL ESTER5 RACETRACK DIESEL 15W-40** is a premium-quality multigrade engine oil designed for optimal performance in engines that operate continuously under extreme conditions. It is specifically formulated for turbocharged and direct injection engines, providing reliable protection in high-stress environments.

### APPLICATION:

**SAVSOL ESTER5 RACETRACK DIESEL 15W-40** Engine Oil is specifically recommended for high-performance turbocharged engines found in modern vehicles that operate under challenging conditions.

### SPECIFICATION & APPROVALS:

**SAVSOL ESTER5 RACETRACK DIESEL 15W-40** Meets the following specification

- |                            |                      |
|----------------------------|----------------------|
| ➤ API CI-4 PLUS/SL         | ➤ MB 228.3           |
| ➤ ACEA E7-12/16            | ➤ MTU Type 2         |
| ➤ JASO DH-1                | ➤ Global DHD-1       |
| ➤ Cummins CES 20076/77/78, | ➤ Caterpillar ECF-1A |
| ➤ MAN 3275                 |                      |

### ADVANTAGES:

**SAVSOL ESTER5 RACETRACK DIESEL 15W-40** Offers following Advantages:

- Superior engine protection on critical engine parts.
- Exceptional cleansing even at longer drain interval periods.
- Helps to remove the sludge faster than the conventional oils.
- Improves engine efficiency and reduce the deposits.
- Neutralizes the corrosive combustion acids efficiently and protects the engine parts. Its highly effective & robust synthetic formula reduces the friction and maximizes the engine performance.

# SAVSOL ESTER5 RACETRACK DIESEL 15W-40

## TECHNICAL SPECIFICATIONS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Bright & Clear
Colour ASTM	D1500	L4.0
Density @ 29.5°C, gm/cc	D4052	0.8607
Kinematic Viscosity @ 40°C, cSt	D445	102.40
Kinematic Viscosity @ 100°C, cSt	D445	14.39
Viscosity Index	D2270	145
TBN, mgKOH/gm	D2896	11.27
Flash Point, °C	D92	232
Pour Point, °C	D97	-33

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

### STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

### ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 17<sup>th</sup> July 2024