

## SAVSOL ESTER5 TRACTOR SPECIAL POWER 15W-40

### DESCRIPTION:

**SAVSOL ESTER5 TRACTOR SPECIAL POWER 15W-40** is a high-performance, multi-grade engine oil engineered to deliver exceptional protection and performance for agricultural machinery. Formulated with premium quality base oils and advanced additives, this engine oil is designed to meet the stringent TREM-IV Emission Standard, ensuring optimal engine efficiency and reduced environmental impact.

### APPLICATION:

**SAVSOL ESTER5 TRACTOR SPECIAL POWER 15W-40** Engine Oil is suitable for use in a variety of agricultural machinery and heavy-duty vehicles operating in harsh conditions, including tractors, harvesters, and other farming equipment.

### SPECIFICATION & APPROVALS:

**SAVSOL ESTER5 TRACTOR SPECIAL POWER 15W-40** exceed the following specifications

- |                                  |                                  |
|----------------------------------|----------------------------------|
| ➤ API CI-4 Plus/CI-4/ CH-4/ CG-4 | ➤ MAN 3275                       |
| ➤ Cummins 20076/20077/20078      | ➤ Renault VI RL D-2              |
| ➤ VOLVO VDS-3                    | ➤ Mack EO-N                      |
| ➤ ACEA E7-04/E2-96               | ➤ DDC93K214                      |
| ➤ Caterpillar CAT ECF-1A/ECF-2   | ➤ Daimler DTFR 15B110 (MB 228.3) |

### ADVANTAGES:

**SAVSOL ESTER5 TRACTOR SPECIAL POWER 15W-40** offers the following advantages:

- Superior engine protection on critical engine parts.
- Exceptional cleansing even at longer drain interval periods.
- Helps to remove the sludge faster than the conventional oils.
- Improves engine efficiency and reduce the deposits.
- Neutralizes the corrosive combustion acids efficiently and protects the engine parts.

## SAVSOL ESTER5 TRACTOR SPECIAL POWER 15W-40

### TECHNICAL SPECIFICATIONS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Bright & Clear
Colour ASTM	D1500	L 3.5
Density @ 29.5°C, gm/cc	D4052	0.8590
Kinematic Viscosity @ 40°C, cSt	D445	96.47
Kinematic Viscosity @ 100°C, cSt	D445	14.36
Viscosity Index	D2270	154
Flash Point, °C	D92	238
Pour Point, °C	D97	-33
Total Base Number, mg KOH/gm	D2896	10.25

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

### STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

### ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 14<sup>th</sup> Jan 2025