

SAVSOL PREMIUM HD XTRA 15W-40

DESCRIPTION:

SAVSOL PREMIUM HD XTRA 15W-40 is a high-performance multigrade engine oil, formulated with premium quality base oils and top-tier additives. Specifically designed to meet the BS-IV Emission Standard, this engine oil provides superior protection and enhanced performance, even under the most severe operating conditions.

APPLICATION:

SAVSOL PREMIUM HD XTRA 15W-40 Engine Oil recommended for high performance engines of Turbo charged & Naturally charged with cooled EGR (Exhaust Gas Re-circulator) & SCR After Treatment Systems, Diesel Gen-Sets, Engines operating under heavy load for construction machinery and farm equipment.

SPECIFICATION & APPROVALS:

SAVSOL PREMIUM HD XTRA 15W-40 has following licence and approvals:

- API CI-4 Plus/CI-4/ CH-4/ CG-4
- Mack EO-N
- Daimler DTFR 15B110 (MB 228.3)
- Renault VI RL D-2
- Cummins 20076/20077/20078
- VOLVO VDS-3
- JASO DH-1

SAVSOL PREMIUM HD XTRA 15W-40 Meets the following specifications

- API CI-4 Plus/CI-4/ CH-4/ CG-4
- MAN 3275
- ACEA E7-04/E2-96
- DDC93K214
- Caterpillar CAT ECF-1A/ECF-2

ADVANTAGES:

SAVSOL PREMIUM HD XTRA 15W-40 offers the following advantages:

- Superior engine protection on critical engine parts.
- Exceptional cleansing even at longer drain interval periods.
- Helps to remove the sludge faster than the conventional oils.
- Improves engine efficiency and reduce the deposits.
- Neutralizes the corrosive combustion acids efficiently and protects the engine parts.

SAVSOL PREMIUM HD XTRA 15W-40

TECHNICAL SPECIFICATIONS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Bright & Clear
Colour ASTM	D1500	L 3.5
Density @ 29.5°C, gm/cc	D4052	0.8590
Kinematic Viscosity @ 40°C, cSt	D445	96.47
Kinematic Viscosity @ 100°C, cSt	D445	14.36
Viscosity Index	D2270	154
Flash Point, °C	D92	238
Pour Point, °C	D97	-33
Total Base Number, mg KOH/gm	D2896	10.25

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 14th Jan 2025