

## SAVSOL SUPER TURBO 20W-40

### DESCRIPTION:

**SAVSOL SUPER TURBO 20W-40** is a high-performance multi-grade engine oil specifically designed for modern turbocharged engines. It is formulated to provide superior protection to engines operating under extreme conditions, ensuring longevity and efficiency even in high-stress environments. This product is particularly suitable for agricultural machinery, trucks, and other commercial vehicles with diesel engines.

### APPLICATION:

**SAVSOL SUPER TURBO 20W-40** Engine Oil recommended for high performance engines of Turbo charged & Naturally aspirated, Diesel Gen-Sets, Engines operating under heavy load for construction machinery, farm equipment's and tractors.

### SPECIFICATION & APPROVALS:

**SAVSOL SUPER TURBO 20W-40** Meets the following specifications

- API CF-4/CE/SG

### ADVANTAGES:

**SAVSOL SUPER TURBO 20W-40** offers the following advantages:

- Excellent Anti-wear, anti-oxidant and detergency properties.
- Superior engine protection on critical engine parts.
- Minimizes sludge formation.
- Improves engine efficiency and reduce the deposits.
- Higher soot dispersancy characteristics.
- Extended Drain interval
- Provides complete engine protection across different engine speeds & conditions.

# SAVSOL SUPER TURBO 20W-40

## TECHNICAL SPECIFICATIONS

| PROPERTIES                       | ASTM TEST METHOD | TYPICAL VALUES |
|----------------------------------|------------------|----------------|
| Appearance                       | Visual           | Bright & Clear |
| Colour                           | Visual           | RED            |
| Density @ 29.5°C, gm/cc          | D4052            | 0.8760         |
| Kinematic Viscosity @ 40°C, cSt  | D445             | 120.40         |
| Kinematic Viscosity @ 100°C, cSt | D445             | 14.46          |
| Viscosity Index                  | D2270            | 116            |
| Flash Point, °C                  | D92              | 232            |
| Pour Point, °C                   | D97              | -24            |
| Total Base Number, mg KOH/gm     | D2896            | 10.50          |

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

### STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

### ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 14<sup>th</sup> Jan 2025