

SAVSOL TRACTOR SPECIAL PLUS 15W-40

DESCRIPTION:

SAVSOL TRACTOR SPECIAL PLUS 15W-40 is a premium quality, multi-grade engine oil formulated to provide outstanding performance and protection for agricultural engines, particularly those operating under extreme conditions. This engine oil is ideal for use in turbocharged and direct injection engines that experience high stress and heavy load operations.

APPLICATION:

SAVSOL TRACTOR SPECIAL PLUS 15W-40 Engine Oil is designed for agricultural tractors and machinery, especially those with turbocharged and direct injection engines, operating under extreme and continuous stress conditions.

This oil is suitable for a wide range of high-performance diesel engines requiring API CH-4/SJ, or earlier specifications.

SPECIFICATION & APPROVALS:

SAVSOL TRACTOR SPECIAL PLUS 15W-40 Meets the following specifications

- | | |
|-----------------------------|-------------------------|
| ➤ API CH-4 / CG-4 / SL / SJ | ➤ CAT ECF-1 |
| ➤ MB 228.3/229.1 | ➤ Cummins 20076 / 20077 |
| ➤ Man 3275 | ➤ VOLVO VDS-2 |
| ➤ MTU Type 2 | ➤ Mack EO-M Plus |

ADVANTAGES:

SAVSOL TRACTOR SPECIAL PLUS 15W-40 offers the following advantages:

- Superior engine protection on critical engine parts.
- Exceptional cleansing even at longer drain interval periods.
- Helps to remove the sludge faster than the conventional oils.
- Improves engine efficiency and reduce the deposits.
- Neutralizes the corrosive combustion acids efficiently and protects the engine parts. Its highly effective & robust synthetic formula reduces the friction and maximizes the engine performance.
- Extended Drain interval

SAVSOL TRACTOR SPECIAL PLUS 15W-40

TECHNICAL SPECIFICATIONS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Bright & Clear
Colour ASTM	D1500	L 3.5
Density @ 29.5°C, gm/cc	D4052	0.8675
Kinematic Viscosity @ 40°C, cSt	D445	107.5
Kinematic Viscosity @ 100°C, cSt	D445	14.25
Viscosity Index	D2270	135
Flash Point, °C	D92	230
Pour Point, °C	D97	-33
Total Base Number, mg KOH/gm	D2896	11.10

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 14th Jan 2025