

SAVSOL ULTRA PREMIUM PLUS 15W-40

DESCRIPTION:

SAVSOL ULTRA PREMIUM PLUS 15W-40 is advanced Diesel Engine Oil delivers extraordinary performance in newer and older heavy duty diesel engines exceeding the requirements of API CK-4/CJ-4/CI-4 Plus/CI-4 and CH-4. It is specially engineered and formulated to provide protection and also the performance to engines having After Treatment Devices including Exhaust Gas Recirculation (EGR) and Diesel Particulate Filter (DPF), Selective Catalytic Reduction (SCR) systems to meet the BS VI Requirements.

APPLICATION:

SAVSOL ULTRA PREMIUM PLUS 15W-40 is designed for use in a wide range of vehicles and equipment, providing excellent protection and performance. It is backward compatible with BS-IV/EURO-IV engines and is highly suitable for heavy-duty diesel engines, including those equipped with advanced after-treatment systems such as EGR, DPF, and SCR. This oil is ideal for on-highway heavy-duty trucking and off-highway applications, including industries like trucking, mining, construction, agriculture, and marine. It performs well in both high-speed, high-load on-highway applications as well as short-haul pick-up and delivery services. Additionally, **SAVSOL ULTRA PREMIUM PLUS 15W-40** excels in off-highway applications that operate under severe low-speed and heavy-load conditions. This versatile oil also meets the demands of high-performance gasoline engines requiring API SN specifications, making it suitable for mixed fleet operations.

SPECIFICATION & APPROVALS:

SAVSOL ULTRA PREMIUM PLUS 15W-40 has following licence and approvals:

- API CK-4/CJ-4/CI-4PLUS/CI-4/CH-4/SN
- VOLVO VDS-4.5
- CUMMINS CES 20086
- MACK EOS 4.5

It exceeds the specifications of the following OEMs:

- ACEA E9
- MAN 3275.1
- FORD WSS-M2C171-F1
- CATERPILLAR ECF -3
- RENAULT RLD-4

SAVSOL ULTRA PREMIUM PLUS 15W-40

ADVANTAGES:

SAVSOL ULTRA PREMIUM PLUS 15W-40 Offers following Advantages:

- Excellent wear protection.
- Extended ODI performance.
- Outstanding engine efficiency, long engine and oil life.
- Lower oil consumption leads to reduced maintenance cost.
- Protection to After Treatment Devices (EGR, DPF, DOC & SCR etc)
- Longer gasket and seal life.
- Excellent soot and viscosity control.

TECHNICAL SPECIFICATIONS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Bright & Clear
Colour ASTM	ASTM D1500	L3.0
Density @ 29.5°C, gm/cc	ASTM D4052	0.8670
Kinematic Viscosity @ 40°C, cSt	ASTM D445	101.0
Kinematic Viscosity @ 100°C, cSt	ASTM D445	15.15
Viscosity Index	ASTM D2270	158
Flash Point, °C	ASTM D92	228
Pour Point, °C	ASTM D97	-33
Total Base Number, mg KOH/gm	ASTM D2896	8.31
CCS Viscosity @ -20°C, cP	ASTM D5293	6400

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the

SAVSOL ULTRA PREMIUM PLUS 15W-40

product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 17th July 2024