

SAVSOL CARGO HD 15W-40

DESCRIPTION:

SAVSOL CARGO HD 15W-40 is a high quality premium multigrade engine oil ideally suited for engines operating continuously under extreme conditions. It is suitable for Turbo charged & Direct Injection engines where the engines observe high stress conditions.

APPLICATION:

SAVSOL CARGO HD 15W-40 Engine Oil recommended for high performance engines of Turbo charged & Naturally charged with EGR (Exhaust Gas Re-circulator), Diesel Generating Sets, Engines operating under heavy load for construction machinery and farm equipment's.

SPECIFICATION & APPROVALS:

SAVSOL CARGO HD 15W-40 Meets the following specifications

- | | |
|-----------------------------|-------------------------|
| ➤ API CH-4 / CG-4 / SL / SJ | ➤ CAT ECF-1 |
| ➤ MB 228.3/229.1 | ➤ Cummins 20076 / 20077 |
| ➤ Man 3275 | ➤ VOLVO VDS-2 |
| ➤ MTU Type 2 | ➤ Mack EO-M Plus |

ADVANTAGES:

SAVSOL CARGO HD 15W-40 offers the following advantages:

- Superior engine protection on critical engine parts.
- Exceptional cleansing even at longer drain interval periods.
- Helps to remove the sludge faster than the conventional oils.
- Improves engine efficiency and reduce the deposits.
- Neutralizes the corrosive combustion acids efficiently and protects the engine parts. Its highly effective & robust synthetic formula reduces the friction and maximizes the engine performance.
- Extended Drain interval
- Provides complete engine protection across different engine speeds & conditions.

SAVSOL CARGO HD 15W-40

TECHNICAL SPECIFICATIONS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Bright & Clear
Colour ASTM	D1500	L 3.5
Density @ 29.5°C, gm/cc	D4052	0.8613
Kinematic Viscosity @ 40°C, cSt	D445	106.6
Kinematic Viscosity @ 100°C, cSt	D445	14.43
Viscosity Index	D2270	139
Flash Point, °C	D92	236
Pour Point, °C	D97	-30
Total Base Number, mg KOH/gm	D2896	7.50

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 14th Jan 2025