

SAVSOL CARGO SPECIAL

DESCRIPTION:

SAVSOL CARGO SPECIAL 15W-40 is a high-quality multigrade engine oil, specifically formulated for the lubrication of turbocharged and naturally aspirated engines that operate under extreme conditions. It provides enhanced performance and protection in a wide range of operating temperatures, ensuring long engine life and optimal performance.

APPLICATION:

SAVSOL CARGO SPECIAL 15W-40 Engine Oil recommended for high performance engines of Turbo charged & Naturally aspirated, Diesel Gen-Sets, Engines operating under heavy load for construction machinery, farm equipment's and tractors.

SPECIFICATION & APPROVALS:

SAVSOL CARGO SPECIAL 15W-40 Meets the following specifications

- API CF-4/CE/SG

ADVANTAGES:

SAVSOL CARGO SPECIAL 15W-40 offers the following advantages:

- Excellent Anti-wear, anti-oxidant and detergency properties.
- Superior engine protection on critical engine parts.
- Minimizes sludge formation.
- Improves engine efficiency and reduce the deposits.
- Higher soot dispersancy characteristics.
- Extended Drain interval
- Provides complete engine protection across different engine speeds & conditions.

SAVSOL CARGO SPECIAL

TECHNICAL SPECIFICATIONS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Bright & Clear
Colour ASTM	D1500	L 3.5
Density @ 29.5°C, gm/cc	D4052	0.8721
Kinematic Viscosity @ 40°C, cSt	D445	108.7
Kinematic Viscosity @ 100°C, cSt	D445	14.29
Viscosity Index	D2270	134
Flash Point, °C	D92	238
Pour Point, °C	D97	-27
Total Base Number, mg KOH/gm	D2896	6.35

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 14th Jan 2025