

SAVSOL CHAIN LUBE

DESCRIPTION:

SAVSOL CHAIN LUBE is specially developed for the lubrication of high-speed motor cycle chains and other chains operating under high loads. It is formulated with special additives which provide protection against rust & corrosion, wear and high Pressure.

SAVSOL CHAIN LUBE penetrates deeply in to chain pin and bushing areas, sets to form an adhesive long lasting lubricating film.

APPLICATION:

SAVSOL CHAIN LUBE is specially designed for lubrication of bike chains and sprockets. It is suitable for O-ring and X-ring chains. Also recommended for rope drives, hoists and sliding surfaces.

ADVANTAGES:

SAVSOL CHAIN LUBE delivers following benefits:

- Reduces noise and vibration of chain.
- Outstanding corrosion & wear protection.
- No oil dripping from chain.
- Reduces friction and wear.
- Superior adhesive property and resistant to throw-off.
- Extends chain life.
- Very strong adherence to chain even at high speeds.
- Harmless to metals and most type of elastomers.
- Does not contain chlorinated solvents. □
- Aerosol formulation uses propellant, provided with extension tube for precise and controlled application of chain lube and film thickness.

DIRECTIONS OF USE:

1. Clean the chain by using chain cleaner or brush.
2. Shake spray can at least 5-6 times of SAVSOL CHAIN before use.
3. Apply on whole length of inner chain.
4. Allow excess to drip and wait for the lube to penetrate before running the chain.
5. Refer OEM's instructions for the application.

SAVSOL CHAIN LUBE

TECHNICAL SPECIFICATIONS

PROPERTIES	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear
Density @ 29.5°C, gm/cc	D4052	0.8690
Base Fluid Viscosity @40 0C, cSt	D445	360
Four Ball Weld Load, N	D2596	3089
Lower Operating Temperature, 0C	---	-20
Upper Operating Temperature, 0C	---	200

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap

Rev.No.00 dtd 29th June .2024.