

SAVSOL ESTER5 ULTRA PREMIUM PLUS 10W-30

DESCRIPTION:

SAVSOL ESTER5 ULTRA PREMIUM PLUS 10W-30 is advanced Diesel Engine Oil delivers extraordinary performance in newer and older heavy duty diesel engines meeting the requirements of API CK-4/CJ- 4/CI-4 Plus/CI-4 and CH-4. It is specially engineered and formulated to provide protection and also the performance to engines having After Treatment Devices including Exhaust Gas Recirculation (EGR) and Diesel Particulate Filter (DPF), Selective Catalytic Reduction (SCR) systems to meet the BS VI Requirements.

APPLICATION:

SAVSOL ESTER5 ULTRA PREMIUM PLUS 10W-30 is recommended for:

- Heavy duty diesel engines, including those equipped with after treatment systems and EGR, DPF & SCR.
- On-highway heavy-duty trucking and off-highway applications including mining, construction, agriculture and marine.
- On-highway applications operating in both high speed/high load and short haul pick- up/delivery service.
- Off-highway applications operating in severe low speed/heavy load conditions.
- Backward compatible with BS-IV/EURO-IV engines.

SPECIFICATION & APPROVALS:

SAVSOL ESTER5 ULTRA PREMIUM PLUS 10W-30 Meets the following specifications

- | | |
|----------------------|---------------------|
| ➤ API CK-4 / SN | ➤ CAT ECF-3 |
| ➤ ACEA E9 | ➤ Cummins CES 20086 |
| ➤ MAN 3275.1 | ➤ VOLVO VDS-4.5 |
| ➤ Renault RLD-4 | ➤ Mack EOS 4.5 |
| ➤ Ford WSS-M2C171-F1 | |

ADVANTAGES:

SAVSOL ESTER5 ULTRA PREMIUM PLUS 10W-30 offers the following advantages:

- Excellent wear protection.
- Extended ODI performance.
- Outstanding engine efficiency, long engine and oil life.

SAVSOL ESTER5 ULTRA PREMIUM PLUS

10W-30

- Lower Oil Consumption lead to reduced maintenance cost
- Protection to After Treatment Devices (EGR, DPF, DOC & SCR etc)
- Longer gasket and seal life.
- Excellent soot and viscosity control.

TECHNICAL SPECIFICATIONS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Bright & Clear
Colour ASTM	D1500	L 3.5
Density @ 29.5°C, gm/cc	D4052	0.8540
Kinematic Viscosity @ 40°C, cSt	D445	80.78
Kinematic Viscosity @ 100°C, cSt	D445	11.98
Viscosity Index	D2270	142
Flash Point, °C	D92	224
Pour Point, °C	D97	-36
Total Base Number, mg KOH/gm	D2896	8.20

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 14th Jan 2025