

SAVSOL UTTO

DESCRIPTION:

SAVSOL UTTO is a premium high-performance Universal Tractor Transmission Oil (UTTO) specially designed with advanced anti-wear and extreme pressure technology for tractors and off-road equipment's.

APPLICATION:

SAVSOL UTTO is recommended for Tractors, Agriculture & Forest Equipment transmissions, drives and hydraulic systems. SAVSOL UTTO is Suitable for Tractors of Mahindra & Mahindra, Swaraj, TAFE, Escorts and many more.

SPECIFICATIONS & APPROVALS:

SAVSOL UTTO meets the requirements of:

- | | |
|----------------------------------|----------------------------------|
| ➤ Massey Ferguson | ➤ Kubota |
| ➤ Ford New Holland | ➤ John Deere |
| ➤ J.I. Case / Case International | ➤ Volvo |
| ➤ Caterpillar-T02 | ➤ Hydraulic OEMs: Sperry Vickers |
| ➤ Saucer Sundstrand / Danfoss | ➤ API GL-4 |
| ➤ Allison C-4 | |

ADVANTAGES:

SAVSOL UTTO delivers following advantages:

- Outstanding low temperature performance.
- Excellent resistance to oxidation breakdown caused by heat.
- Exceptional anti-wear properties.
- Resistance to rust and corrosion.
- Excellent system cleanliness.

SAVSOL UTTO

TECHNICAL SPECIFICATIONS - SAVSOL UTTO

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear
Colour ASTM	D1500	L 2.0
Density @ 29.5°C, gm/cc	D4052	0.8640
Kinematic Viscosity @ 40°C, cSt	D445	90.77
Kinematic Viscosity @ 100°C, cSt	D445	11.03
Viscosity Index	D2270	107
Flash Point, °C	D92	222
Pour Point, °C	D97	-24

The above details are typical results under normal production conditions and could vary depending upon external factors.

The information provided herein is subject to change without notification depending upon change in specifications of the products.

We make no warranties other than the specifications of the product, express or implied, and hereby disclaim all express or implied warranties, including warranty of any recommendations, merchantability and fitness of the product for a particular purpose.

We shall not be liable for any direct, indirect, incidental, punitive or consequential damages unless otherwise agreed by us in writing.

Storage:

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

Environment, Health, and Safety

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point.
- This product is unlikely to present any safety & health hazard when effectively used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 11th July 2025.